




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04B 7/185, G01S 5/02</b>		A1	(11) International Publication Number: <b>WO 97/33382</b>
			(43) International Publication Date: 12 September 1997 (12.09.97)
(21) International Application Number: PCT/US97/03512		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 7 March 1997 (07.03.97)			
(30) Priority Data: 08/612,582 8 March 1996 (08.03.96) US 08/759,523 4 December 1996 (04.12.96) US			
(71) Applicant (for all designated States except US): SNAPTRACK, INC. [US/US]; Suite 250, 4040 Moorpark Avenue, San Jose, CA 95117 (US).			
(72) Inventor; and			
(75) Inventor/Applicant (for US only): KRASNER, Norman, F. [US/US]; 117 Coventry Court, San Carlos, CA 94070 (US).			
(74) Agents: SCHELLER, James, C., Jr. et al.; Blakely, Sokoloff, Taylor & Zafman L.L.P., 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).			
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: AN IMPROVED GPS RECEIVER UTILIZING A COMMUNICATION LINK



## (57) Abstract

A precision carrier frequency signal for calibrating a local oscillator (56) of a GPS receiver which is used to acquire GPS signals. The precision carrier frequency signal is used to calibrate the local oscillator such that the output of the local oscillator, which is used to acquire GPS signals, is modified by a reference signal generated from the precision carrier frequency signal. The GPS receiver locks (53) to this precision carrier frequency signal and generates the reference signal. In another aspect of the invention, satellite almanac data is transmitted to a remote GPS receiver unit (20) from a base station (12) via a communication link. The remote GPS receiver unit uses this satellite almanac data to determine approximate Doppler data for satellites in view of the remote GPS receiver unit.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## AN IMPROVED GPS RECEIVER UTILIZING A COMMUNICATION LINK

### BACKGROUND OF THE INVENTION

#### RELATED APPLICATIONS

This application is a continuation-in-part of U.S. Patent Application Serial No. 08/612,582, filed on March 8, 1996 by Norman F. Krasner.

This application is also related to and hereby claims the benefit of the filing date of a provisional patent application by the same inventor, Norman F. Krasner, which application is entitled Low Power, Sensitive Pseudorange Measurement Apparatus and Method for Global Positioning Satellites Systems, Serial No. 60/005,318, filed October 9, 1995.

#### 1. FIELD OF THE INVENTION

The present invention relates to receivers capable of determining position information of satellites and, in particular, relates to such receivers which find application in global positioning satellite (GPS) systems.

#### 2. BACKGROUND ART

GPS receivers normally determine their position by computing relative times of arrival of signals transmitted simultaneously from a multiplicity of GPS (or NAVSTAR) satellites. These satellites transmit, as part of their message, both satellite positioning data as well as data on clock timing, so-called "ephemeris" data. The process of searching for and acquiring GPS signals, reading the ephemeris data for a multiplicity of satellites and computing the location of the receiver from this data is time consuming, often requiring several minutes. In many cases, this lengthy processing time is unacceptable and, furthermore, greatly limits battery life in micro-miniaturized portable applications.

Another limitation of current GPS receivers is that their operation is limited to situations in which multiple satellites are clearly in view, without obstructions, and where a good quality antenna is properly positioned to receive such signals. As such, they normally are unusable in portable, body

-2-

mounted applications; in areas where there is significant foliage or building blockage; and in in-building applications.

There are two principal functions of GPS receiving systems: (1) computation of the pseudoranges to the various GPS satellites, and (2) computation of the position of the receiving platform using these pseudoranges and satellite timing and ephemeris data. The pseudoranges are simply the time delays measured between the received signal from each satellite and a local clock. The satellite ephemeris and timing data is extracted from the GPS signal once it is acquired and tracked. As stated above, collecting this information normally takes a relatively long time (30 seconds to several minutes) and must be accomplished with a good received signal level in order to achieve low error rates.

Virtually all known GPS receivers utilize correlation methods to compute pseudoranges. These correlation methods are performed in real time, often with hardware correlators. GPS signals contain high rate repetitive signals called pseudorandom (PN) sequences. The codes available for civilian applications are called C/A codes, and have a binary phase-reversal rate, or "chipping" rate, of 1.023 MHz and a repetition period of 1023 chips for a code period of 1 msec. The code sequences belong to a family known as Gold codes. Each GPS satellite broadcasts a signal with a unique Gold code.

For a signal received from a given GPS satellite, following a downconversion process to baseband, a correlation receiver multiplies the received signal by a stored replica of the appropriate Gold code contained within its local memory, and then integrates, or lowpass filters, the product in order to obtain an indication of the presence of the signal. This process is termed a "correlation" operation. By sequentially adjusting the relative timing of this stored replica relative to the received signal, and observing the correlation output, the receiver can determine the time delay between the received signal and a local clock. The initial determination of the presence of such an output is termed "acquisition." Once acquisition occurs, the process enters the "tracking" phase in which the timing of the local reference is adjusted in small amounts in order to maintain a high correlation output. The correlation output during the tracking phase may be viewed as the GPS

signal with the pseudorandom code removed, or, in common terminology, "despread." This signal is narrow band, with bandwidth commensurate with a 50 bit per second binary phase shift keyed data signal which is superimposed on the GPS waveform.

The correlation acquisition process is very time consuming, especially if received signals are weak. To improve acquisition time, many GPS receivers utilize a multiplicity of correlators (up to 12 typically) which allows a parallel search for correlation peaks.

Another approach to improve acquisition time is described in U.S. Patent No. 4,445,118. This approach uses the transmission of Doppler information from a control basestation to a remote GPS receiver unit in order to aid in GPS signal acquisition. While this approach does improve acquisition time, the Doppler information is accurate for only a short period of time as the GPS satellites orbit the earth at relatively high speeds. Thus, a further transmission of Doppler information will be necessary in order for a remote unit to use accurate Doppler information.

An approach for improving the accuracy of the position determination by a remote GPS receiver unit is also described in U.S. Patent No. 4,445,118, referred to as the Taylor patent. In the Taylor patent, a stable frequency reference is transmitted to a remote GPS receiver unit from a basestation in order to eliminate a source of error due to a poor quality local oscillator at the remote GPS receiver unit. This method uses a special frequency shift keyed (FSK) signal that must be situated in frequency very close to the GPS signal frequency. As shown in Figure 4 of the Taylor patent, the special FSK signal is about 20 MHz below the 1575 MHz GPS signal. Moreover, the approach described in the Taylor patent uses a common mode rejection mechanism in which any error in the local oscillator (shown as L.O. 52) of the receiver will appear in both the GPS channel and the reference channel and hence be canceled out. There is no attempt to detect or measure this error. This approach is sometimes referred to as a homodyne operation. While this approach provides some advantages, it requires that the two channels be closely matched, including closely matched in frequency. Moreover, this approach requires that both

-4-

frequencies remain fixed, so frequency hopping techniques are not compatible with this approach.

#### SUMMARY

In one aspect of the present invention, a mobile GPS receiver receives a precision carrier frequency signal from a source providing the precision carrier frequency signal. The receiver locks to this frequency signal and provides a reference signal which is used to calibrate (e.g., stabilize or correct) a local oscillator that is used to acquire GPS signals. An apparatus which practices this aspect includes, in one embodiment, a first antenna which receives GPS signals and a downconverter coupled to the first antenna. The downconverter is coupled to a local oscillator which provides a first reference signal to the downconverter. The apparatus also includes a second antenna for receiving a precision carrier frequency signal from a source providing the precision carrier frequency signal and an automatic frequency control (AFC) circuit coupled to the second antenna. The AFC circuit provides a second reference signal to the local oscillator to calibrate the first reference signal which is used to acquire GPS signals received through the first antenna. The frequency of the precision carrier frequency signal may vary from transmission to transmission.

One embodiment of the present invention provides a method for determining the position of a remote GPS receiver by transmitting GPS satellite information, including satellite almanac data, to the remote unit or mobile GPS unit from a basestation via a data communication link. The satellite almanac data is then used to determine Doppler data for satellites in view of the remote unit. The remote unit uses this Doppler data and received GPS signals from in view satellites to subsequently compute pseudoranges to the satellites. The computed pseudoranges are then transmitted to the basestation where the position of the remote unit is calculated. Various embodiments of apparatuses which can perform this method are also described.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings in which references indicate similar elements and in which:

Figure 1A is a block diagram of the major components of a remote or mobile GPS receiving system utilizing the methods of the present invention, and shows data links that may exist between a basestation and the remote.

Figure 1B is a block diagram of an alternative GPS mobile unit.

Figure 1C is a block diagram of another alternative GPS mobile unit.

Figures 2A and 2B provide two alternatives for the RF and IF portions of a receiver which is an embodiment of the present invention.

Figure 3 shows a flow chart of the major operations (e.g. software operations) performed by the programmable DSP processor in accordance with the methods of the present invention.

Figures 4A-4E illustrates the signal processing waveforms at various stages of processing according to the methods of the present invention.

Figure 5A illustrates a basestation system in one embodiment of the present invention.

Figure 5B illustrates a basestation system in an alternative embodiment of the present invention.

Figure 6A illustrates a GPS mobile unit having, according to one aspect of the present invention, local oscillator calibration.

Figures 6B and 6C show other embodiments of GPS mobile units having local oscillator calibration.

Figure 7 is a flow chart which shows a power management method for a mobile unit according to one embodiment of the present invention.

Figure 8 shows a method for deriving Doppler information for satellites in view from satellite almanac data provided to a mobile unit.

#### DETAILED DESCRIPTION OF THE INVENTION

This invention concerns apparatuses and methods for computing the position of a mobile, or remote, object in a manner that results in the remote hardware having very low power dissipation and the ability to operate with very low received signal levels and yet provide accurate measurements of position information. That is, power consumption is reduced while receiver sensitivity and accuracy is increased. This is also made possible by the receipt and use at the remote unit of a stable frequency communication signal. This is made possible by the implementation of the remote receiving

functions, as shown in Figure 1A, as well as the transmission of satellite almanac information from a separately located basestation 10 to the remote or GPS mobile unit 20.

It should be noted that pseudoranges may be used to compute the remote's geographical position in many different ways. Three examples are:

1. Method 1: By re-transmitting the satellite data messages to the remote 20 from the basestation 10, the remote 20 may combine this information with the pseudorange measurements to compute its position. See, for example, U.S. patent No. 5,365,450, which is incorporated herein by reference. Typically, the remote unit 20 performs the computation of position in the remote 20.
2. Method 2: The remote 20 may gather the satellite ephemeris data from the reception of GPS signals in the normal manner that is commonly practiced in the art. This data, which typically is valid for one to two hours, may be combined with pseudorange measurements to complete, typically in the remote unit, the position calculation.
3. Method 3: The remote 20 may transmit over a communications link 16 the pseudoranges to the basestation 10 which can combine this information with the satellite ephemeris data to complete the position calculation. See, for example, U.S. Patent No. 5,225,842, which is incorporated herein by reference.

In approaches (or Methods) 1 and 3, it is assumed that the basestation 10 and remote 20 have a common view of all satellites of interest and are positioned close enough to one another to resolve a time ambiguity associated with the repetition rate of the GPS pseudorandom codes. This will be met for a range between basestation 10 and remote 20 of  $1/2$  times the speed of light times the PN repetition period (1 millisecond), or about 150 km.

In order to explain the current invention, it is assumed that method 3 is utilized to complete the position calculation. However, upon review of this Specification, it will be appreciated by those skilled in the art that the various aspects and embodiments of the present invention could be



used with any of the above three Methods as well as other approaches. For example, in a variation of Method 1, satellite data information such as data representative of satellite ephemeris may be transmitted by a basestation to a remote unit, and this satellite data information may be combined with pseudo ranges, computed according to the present invention from buffered GPS signals, to provide a latitude and longitude (and in many cases also an altitude) for the remote unit. It will be appreciated that the position information received from the remote may be limited to latitude and longitude or may be extensive information which includes latitude, longitude, altitude, velocity and bearing of the remote. Moreover, the local oscillator correction and/or the power management aspects of the present invention may be utilized in this variation of Method 1. Furthermore, satellite almanac information may be transmitted to the remote unit 20 and utilized by the remote unit 20 in accordance with aspects of the present invention.

Under Method 3, the basestation 10 commands the remote 20 to perform a measurement via a message transmitted over a data communications link 16 as shown in Figure 1A. The message from the basestation 10 which commands the remote 20 may typically also specify an identification of the particular satellites in view or other initialization data. The basestation 10 may also send within this message (or may have previously sent) satellite almanac information, which is a form of satellite data information. This satellite almanac information typically includes a description of the approximate position versus time of all satellites in the GPS constellation. U.S. Patent No. 4,445,118 describes some of the data which may be included in satellite almanac data. This message is received by a separate modem 22 that is part of the remote unit 20, and it is stored in a memory 30 coupled to a low-power microprocessor 26. The satellite almanac information may then be used to derive Doppler information for satellites in view; this derivation is described further below. The almanac data may be valid for periods up to one month. The microprocessor 26 handles data information transfer between the remote unit processing elements 32-48 and the modem 22, and it controls power management functions within the remote receiver 20, as will be evident in the

subsequent discussion. Normally, the microprocessor 26 sets most or all remote unit 20's hardware to a low power, or power down, state, except when the pseudorange and/or other GPS calculations are being performed, or when an alternative source of power is available. However, the receiver portion of the modem is at least periodically turned on (to full power) to determine if the basestation 10 has sent a command to the remote to determine the remote's position.

The use of this satellite almanac information to derive Doppler information for satellites in view of the remote eliminates the requirement for the remote 20 to search for such Doppler, thereby reducing its processing time by in excess of a factor of 10. The use of the Doppler information also allows the GPS mobile unit 20 to process more quickly a sample of GPS signals and this tends to reduce the amount of time for which the processor 32 must receive full power in order to compute a position information. This alone reduces the power consumed by the remote unit 20 and contributes to improved sensitivity. Additional information may also be sent to the remote 20, including the epochs of the data in the GPS message.

The received data link signal may utilize a precision carrier frequency. The remote receiver 20 may employ, as shown in Figure 6 which is described below, an automatic frequency control (AFC) loop to lock to this carrier and thereby further calibrate its own reference oscillator (e.g., by correcting the output frequency of the GPS L.O. which is used to acquire GPS signals). A message transmission time of 10 msec, with a received signal to noise ratio of 20 dB, will normally allow frequency measurement via an AFC to an accuracy of 10 Hz or better. This will typically be more than adequate for the requirements of the present invention. This feature will also enhance the accuracy of the position calculations which are performed, either conventionally or using the fast convolution methods of the present invention. This feature is described below in further detail.

In one embodiment of the invention, the communication link 16 is a commercially available narrow bandwidth radio frequency communication medium, such as a two-way pager system. This system

may be used in embodiments where the amount of data transmitted between the remote 20 and basestation 10 is relatively small. The amount of data required for the transmission of Doppler (instead of satellite almanac data) and other data (e.g. initialization data such as the identities of the satellites in view) is relatively small and similarly the amount of data required for the position information (e.g., pseudoranges) is relatively small. Consequently, narrowband systems are adequate for this embodiment. Satellite almanac data may be compressed such that the amount of data necessary to describe the approximate position of all satellites in the GPS constellation may be transmitted efficiently in a narrowband width communication system. Those systems which require the transmission of large amounts of data over a short period of time may require a higher bandwidth radio frequency communication medium. These higher bandwidth systems may be required in those embodiments where uncompressed satellite almanac data is transmitted.

It will be appreciated that it may nevertheless be efficient to use a narrowband system even when uncompressed satellite almanac information is transmitted because the almanac information has good accuracy for long periods of time (e.g., a month, typically). Thus, this information may be transmitted once a month and then stored in the GPS mobile unit (e.g., in flash EEPROM memory) and used for the entire month; typically, in this case, this information is stored with a time stamp which indicates the date of receipt of the satellite almanac data. The remote unit may then, when receiving a command to provide its position information, determine whether the satellite almanac data is stale and receive or not receive the transmission of almanac data provided by the basestation. If the data is not stale (e.g. the almanac data, as indicated by its time stamp, is less than a month old or some other predetermined period of time), then the data may be used from storage and receipt of "fresh" satellite almanac data is not necessary and the automatic transmission of such data is ignored. Alternatively, the basestation may determine whether to transmit satellite almanac data by keeping a list of the remote units which have been sent satellite almanac data and a time stamp indicating the last transmission of satellite almanac data for each such remote unit. The

-10-

basestation can then determine whether to transmit satellite almanac data with a position fix command based upon the staleness of the last satellite almanac data stored at the particular remote. If the almanac data at the particular remote is not stale (e.g., it is less than one month old) then the position fix command without the almanac data is transmitted from the basestation to the remote. If the almanac data is stale, then current satellite almanac data is transmitted to the remote unit.

Once the remote 20 receives a command (e.g., from the basestation 10) for GPS processing together with the satellite almanac information (or determines it may use a locally stored version of satellite almanac data), the microprocessor 26 activates the RF to IF Converter 42, Analog to Digital Converter 44 and Digital Snapshot Memory 46 via a Battery and Power Regulator and Power Switches circuit 36 (and controlled power lines 21a, 21b, 21c and 21d) thereby providing full power to these components. This causes the signal from the GPS satellite which is received via antenna 40 to be downconverted to an IF frequency, where it subsequently undergoes digitization. A set of such data, typically corresponding to a duration of 100 milliseconds to 1 second (or even longer), is then stored in a Snapshot Memory 46. The amount of data stored may be controlled by the microprocessor 26 such that more data may be stored in the memory 46 (to obtain better sensitivity) in those situations when conserving power is not as important as obtaining better sensitivity, and less data may be stored in those situations when conservation of power is more important than sensitivity. Typically, sensitivity is more important when the GPS signals may be obstructed partially, and power conservation is less important when a copious power supply (e.g. a car battery) is available. The addressing of this memory 46 to store this data is controlled by a Field Programmable Gate Array integrated circuit 48. Downconversion of the GPS signal is accomplished using a frequency synthesizer 38 which provides local oscillator signal 39 to the converter 42 as discussed further below.

Note that all this time (while the snapshot memory 46 is being filled with the digitized GPS signals from the in view satellites) the DSP microprocessor 32 may be kept in a low power state. The RF to IF

Converter 42 and Analog to Digital Converter 44 are typically only turned on for a short period of time, sufficient to collect and store the data required for pseudorange calculation. After the data collection is complete, these converter circuits are turned off or power is otherwise reduced via controlled power lines 21b and 21c (while the memory 46 continues to receive full power), thus not contributing to additional power dissipation during the actual pseudorange calculation. The pseudorange calculation is then performed using, in one embodiment, a general purpose, programmable digital signal processing IC 32 (DSP), as exemplified by a TMS320C30 integrated circuit from Texas Instruments. This DSP 32 is placed in an active power state by the microprocessor 26 and the circuit 36 via controlled power line 21e prior to performing such calculations.

This DSP 32 differs from others used in some remote GPS units in that it is general purpose and programmable, as compared to specialized custom digital signal processing IC's. Furthermore, the DSP 32 makes possible the use of a Fast Fourier Transform (FFT) algorithm, which permits very rapid computation of the pseudoranges by performing rapidly a large number of correlation operations between a locally generated reference and the received signals. Typically, 2046 such correlations are required to complete the search for the epochs of each received GPS signal. The Fast Fourier Transform algorithm permits a simultaneous and parallel search of all such positions, thus speeding the required computation process by a factor of 10 to 100 over conventional approaches.

Once the DSP 32 completes its computation of pseudoranges for each of the in view satellites, it transmits, in one embodiment of the invention, this information to the microprocessor 26 via interconnect bus 33. At this time the microprocessor 26 may cause the DSP 32 and memory 46 to again enter a low power state by sending an appropriate control signal to the Battery and Power Regulator circuit 36. Then, the microprocessor 26 utilizes a modem 22 to transmit the pseudorange data over a data link 16 to the basestation 10 for final position computation. In addition to the pseudorange data, a time tag may simultaneously be transmitted to the basestation 10 that indicates the elapsed time from the

-12-

initial data collection in the buffer 46 to the time of transmission of the data over the data link 16. This time tag improves the capability of the basestation to compute position calculation, since it allows the computation of the GPS satellite positions at the time of data collection. As an alternative, in accordance with Method 1 above, the DSP 32 may compute the position (e.g. latitude, longitude or latitude, longitude and altitude) of the remote unit and send this data to the microprocessor 26, which similarly relays this data to the basestation 10 via the modem 22. In this case the position computation is eased by the DSP maintaining the elapsed time from the reception of satellite data messages to the time at which the buffer data collection begins. This improves the capability of the remote unit to compute position calculation, since it allows the computation of the GPS satellite positions at the time of data collection.

As shown in Figure 1A, modem 22, in one embodiment, utilizes a separate antenna 24 to transmit and receive messages over data link 16. It will be appreciated that the modem 22 includes a communication receiver and a communication transmitter which are alternatively coupled to the antenna 24. Similarly, basestation 10 may use a separate antenna 14 to transmit and receive data link messages, thus allowing continuous reception of GPS signals via GPS antenna 12 at the basestation 10.

It is expected, in a typical example, that the position calculations in the DSP 32 will require less than a few seconds of time, depending upon the amount of data stored in the digital snapshot memory 46 and the speed of the DSP or several DSPs.

It should be clear from the above discussion that the remote unit 20 need only activate its high power consumption circuits for a small fraction of time, if position calculation commands from the basestation 10 are infrequent. It is anticipated, in at least many situations, that such commands will result in the remote equipment being activated to its high power dissipation state only about 1% of the time or less.

This then allows battery operation for 100 times the length of time that would otherwise be possible. The program commands necessary for the performance of the power management operation are stored in EEPROM 28 or other suitable storage media. This power management

strategy may be adaptable to different power availability situations. For example, when prime power is available the determination of position may occur on a continuing basis.

As indicated above, the digital snapshot memory 46 captures a record corresponding to a relatively long period of time. The efficient processing of this large block of data using fast convolution methods contributes to the ability of the present invention to process signals at low received levels (e.g., when reception is poor due to partial blockage from buildings, trees, etc.). All pseudoranges for visible GPS satellites are computed using this same buffered data. This provides improved performance relative to continuous tracking GPS receivers in situations (such as urban blockage conditions) in which the signal amplitude is rapidly changing.

A slightly different implementation exhibited in Figure 1B dispenses with the microprocessor 26 and its peripherals (RAM 30 and EEPROM 28) and replaces its functionality with additional circuitry contained within a more complex FPGA (field programmable gate array) 49. The structure and operation of the remote unit shown in Figure 1B is described in further detail in U.S. Patent Application Serial No. 08/612,669, filed March 8, 1996 by Norman F. Krasner, now U.S. Patent No. \_\_\_\_\_, which application is hereby incorporated herein by reference. The remote unit of Figure 1B uses the DSP 32a to selectively power on or reduce power to different components according to a power management method such as that shown in Figure 7.

Figure 1C shows another embodiment according to the present invention of a GPS mobile unit which contains many of the same components as the GPS mobile units shown in Figures 1A and 1B.

Figure 1C shows a feature of the present invention which allows the GPS mobile unit to trade off sensitivity for power conservation. As described herein sensitivity of the GPS mobile unit may be increased by increasing the amount of buffered GPS signals which are stored in the memory 46. This is done by acquiring and digitizing more GPS signals and storing this data in the memory 46. While this increased buffering causes more power consumption, it does improve the sensitivity of the

GPS mobile unit. The structure and operation of the remote unit shown in Figure 1C is described in further detail in the above noted U.S. Patent Application Serial No. 08/612,669, filed March 8, 1996.

Representative examples of an RF to IF frequency converter and digitizing system for the mobile GPS unit are shown in Figure 2A and 2B. The structure and operation of these examples shown in Figure 2A and 2B are described in further detail in the above noted U.S. Patent Application Serial No. 08/612,669, filed March 8, 1996.

Details of the GPS signal processing performed in the DSP 32 may be understood with the aid of the flow chart of Figure 3 and the pictorial of Figures 4A, 4B, 4C, 4D and 4E. It will be apparent to those skilled in the art that the machine code, or other suitable code, for performing the signal processing to be described is stored in EPROM 34. Other non-volatile storage devices could also be used. The following assumes that the I/Q sampling of Figure 2A is employed and that the snapshot memory 46 contains two channels of digitized data at 2.048 MHz. The objective of the processing is to determine the timing of the received waveform with respect to a locally generated waveform. Furthermore, in order to achieve high sensitivity, a very long portion of such a waveform, typically 100 milliseconds to 1 second, is processed. It will also be appreciated that the Doppler information which is used in this signal processing may be Doppler information which was derived from stored or recently transmitted satellite almanac data (or may be Doppler information directly transmitted along with the position command to the remote unit so that no Doppler derivation in the remote unit is required). The derivation of Doppler information from satellite almanac data is described further herein in conjunction with Figure 8. Further details concerning the signal processing shown in Figures 3 and 4A-4E are described in the above noted U.S. Patent Application Serial No. 08/612,669, filed March 8, 1996.

A summary of the signal processing described above and shown in Figure 3 and in Figures 4A-4E will now be provided. The GPS signals from one or more in view GPS satellites are received at the remote GPS unit using an antenna on the remote GPS unit. These signals are digitized and stored in a buffer in the remote GPS unit. After storing these signals, a processor performs in one embodiment preprocessing, fast convolution processing, and post processing operations. These processing operations involve:



a) breaking the stored data into a series of blocks whose durations are equal to a multiple of the frame period of the pseudorandom (PN) codes contained within the GPS signals.

b) for each block performing a preprocessing step which creates a compressed block of data with length equal to the duration of a pseudorandom code period by coherently adding together successive subblocks of data, the subblocks having a duration equal to one PN frame; this addition step will mean that the corresponding sample numbers of each of the subblocks are added to one another.

c) for each compressed block, performing a matched filtering operation, which utilizes fast convolution techniques, to determine the relative timing between the received PN code contained within the block of data and a locally generated PN reference signal (e.g. the pseudorandom sequence of the GPS satellite being processed).

d) determining a pseudorange by performing a magnitude-squared operation on the products created from said matched filtering operation and post processing this by combining the magnitude-squared data for all blocks into a single block of data by adding together the blocks of magnitude-squared data to produce a peak.

and e) finding the location of the peak of said single block of data to high precision using digital interpolation methods, where the location is the distance from the beginning of the data block to the said peak, and the location represents a pseudorange to a GPS satellite corresponding to the pseudorandom sequence being processed.

Typically, the fast convolution technique used in processing the buffered GPS signals is a Fast Fourier Transform (FFT) and the result of the convolution is produced by computing the product of the forward transform of the compressed block and a prestored representation of the forward transform of the pseudorandom sequence to produce a first result and then performing an inverse transformation of the first result to recover the result. Also, the effects the Doppler induced time delays and local oscillator induced time errors are compensated for on each compressed block of data by inserting between the forward and inverse Fast Fourier Transform operations, the multiplication of the forward FFT of the compressed blocks by a complex exponential whose phase

-16-

versus sample number is adjusted to correspond to the delay compensation required for the block.

In the foregoing embodiment the processing of GPS signals from each satellite occurs sequentially over time, rather than in parallel. In an alternative embodiment, the GPS signals from all in view satellites may be processed together in a parallel fashion in time.

It is assumed here that the basestation 10 has a common view of all satellites of interest and that it is sufficiently close in range to remote unit 20 in order to avoid ambiguities associated with the repetition period of the C/A PN code. A range of 90 miles will satisfy this criteria. The basestation 10 is also assumed to have a GPS receiver and a good geographical location such that all satellites in view are continuously tracked to high precision.

While several described embodiments of the basestation 10 show the use of a data processing component, such as a computer at the basestation in order to compute position information such as a latitude and a longitude for the mobile GPS unit, it will be appreciated that each basestation 10 may merely relay the information received, such as pseudoranges from a mobile GPS unit, to a central location or several central locations which actually perform the computation of latitude and longitude. In this manner the cost and complexity of these relaying basestations may be reduced by eliminating a data processing unit and its associated components from each relaying basestation. A central location, would include receivers (e.g. telecommunication receivers) and a data processing unit and associated components. Moreover, in certain embodiments, the basestation may be virtual in that it may be a satellite which transmits Doppler information or satellite almanac data to remote units, thereby emulating a basestation in a transmission cell.

Figures 5A and 5B show two embodiments of a basestation according to the present invention. In the basestation shown in Figure 5A, a GPS receiver 501 receives GPS signals through a GPS antenna 501a. The GPS receiver 501, which may be a conventional GPS receiver, provides a timed reference signal which typically is timed relative to GPS signals and also provides satellite almanac data for all the satellites in the constellation of GPS satellites and may provide Doppler information relative to the satellites in view. This GPS receiver 501 is coupled to a disciplined local oscillator 505 which receives the time reference signal 510 and

phase locks itself to this reference. This disciplined local oscillator 505 has an output which is provided to a modulator 506. The modulator 506 also receives the satellite almanac data (or alternatively, Doppler data information signals for each satellite in view of the GPS mobile unit) and/or other satellite data information signals 511. The modulator 506 modulates the satellite almanac data (or alternatively, the Doppler) and/or other satellite data information onto the local oscillator signal received from the discipline local oscillator 505 in order to provide a modulated signal 513 to the transmitter 503. The transmitter 503 is coupled to the data processing unit 502 via interconnect 514 such that the data processing unit may control the operation of the transmitter 503 in order to cause the transmission of satellite data information, such as the satellite almanac information to a GPS mobile unit via the transmitter's antenna 503a. In this manner, a GPS mobile unit may receive the satellite almanac information, the source of which is the GPS receiver 501 and may also receive a high precision local oscillator carrier signal which may be used to calibrate the local oscillator in the GPS mobile unit as shown in Figure 6. It will be appreciated that the basestation may transmit the current satellite almanac data automatically with each transmission of a position fix command to the remote unit. Alternatively the basestation may, as described above, determine whether the remote's stored version of the satellite almanac data is stale and transmit the current almanac data only if the remote's stored version is stale. If a high bandwidth communication system is being used as the communication link (e.g., a cellular telephone system) then the former approach is preferred. If a narrow bandwidth communication system is being used, then the latter approach may be preferred.

The basestation as shown in Figure 5A also includes a receiver 504 which is coupled to receive communication signals from the remote or GPS mobile unit via a communication antenna 504a. It will be appreciated that the antenna 504a may be the same antenna as the transmitter's antenna 503a such that a single antenna serves both the transmitter and the receiver in the conventional fashion. The receiver 504 is coupled to the data processing unit 502 which may be a conventional computer system. The processing unit 502 may also include an interconnect 512 to receive the Doppler and/or other satellite data information from the GPS receiver 511. This information may be utilized in processing the pseudorange information or other information received from the mobile unit via

the receiver 504. This data processing unit 502 is coupled to a display device 508, which may be a conventional CRT. The data processing unit 502 is also coupled to a mass storage device 507 which includes GIS (Geographical Information System) software (e.g. Atlas GIS from Strategic Mapping, Inc. of Santa Clara, California) which is used to display maps on the display 508. Using the display maps, the position of the mobile GPS unit may be indicated on the display relative to a displayed map.

An alternative basestation shown in Figure 5B includes many of the same components shown in Figure 5A. However, rather than obtaining the satellite almanac data or Doppler and/or other satellite data information from a GPS receiver, the basestation of Figure 5B includes a source of satellite almanac data or Doppler and/or other satellite data information 552 which is obtained from a telecommunication link or a radio link in a conventional matter. For example, this information may be obtained from a server site on the Internet. This Doppler and/or satellite information is conveyed over an interconnect 553 to the modulator 506. The other input the modulator 506 shown in Figure 5B is the oscillator output signal from a reference quality local oscillator such as a cesium standard local oscillator. This reference local oscillator 551 provides a precision carrier frequency onto which is modulated the Doppler and/or other satellite data information which is then transmitted via transmitter 503 to the mobile GPS unit.

Although the preceding discussion illustrates a basestation which integrates all functions of satellite data transmission and frequency reference information, in most practical situations this may be partially performed using commercial telecommunication systems, such as cellular or paging systems. For example, most digital cellular systems utilize a very stable local oscillator in their transmitted signals. In this case, a basestation need only gather the satellite data, as in blocks 501 or 552 and send this data over such a cellular system using a conventional wireline modem. The actual modulation functions, including the precision frequency reference transmission, are then performed by the cell site transmitter. This approach results in a very low cost basestation with no special RF circuitry. Similarly, on the remote to basestation link, the cellular system provides the receiving and demodulation functions of block 504 and the basestation need only utilize a modem to receive such data over normal wirelines.

It is an important characteristic of this invention that the transmission frequency and format of the data signals are unimportant, as long as the carrier frequency is very stable. It should also be noted that this carrier frequency may vary from one transmission to the next, as it commonly does in cellular systems, which utilize a large number of frequency channels to service a large number of users. In some cases the carrier frequency may also vary within one call. For example, frequency hopping is utilized in some digital cellular systems. Again, this invention can utilize such signaling, as long as the remote receiver can frequency lock to the stable transmitted frequencies.

Figure 6A shows an embodiment of a GPS mobile unit of the present invention which utilizes the precision carrier frequency signal received through the communication channel antenna 601 which is similar to the antenna 24 shown in Figure 1A. The antenna 601 is coupled to the modem 602, which is similar to the modem 22 in Figure 1A, and this modem 602 is coupled to an automatic frequency control circuit 603 which locks to the precision carrier frequency signal sent by the basestation (which may be considered to be or include a cellular telephone cell site transmitter) described herein according to one embodiment of the present invention. The automatic frequency control circuit 603 provides an output 604, which is typically locked in frequency to the precision carrier frequency. This signal 604 is compared by the comparator 605 to the output of the GPS local oscillator 606, via interconnect 608. The result of the comparison performed by the comparator 605 is an error correction signal 610 which is provided as a correction signal to the GPS local oscillator 606. In this manner, the frequency synthesizer 609 provides a higher quality, calibrated local oscillation signal over interconnect 612 to the GPS down converter 614. It will be appreciated that the GPS local oscillator 606 and the frequency synthesizer 609 may together be considered a local oscillator which provides a GPS clock signal that is inputted to the downconverter to acquire the GPS signals received through the GPS antenna 613. As used herein, "calibrated", "calibrate" or "calibration" refers to either a system which measures and corrects a local oscillator (by using a reference signal derived from a measurement of an error in a local oscillator) or a system which stabilizes a local oscillator signal (e.g., by feeding a local oscillator signal from the communication receiver to frequency synthesizing circuits that generate GPS clock signals which are used to downconvert/acquire GPS signals).

It will be appreciated that the signal provided over interconnect 612 is similar to the local oscillator signal provided by interconnect 39 on Figure 1A to the converter 42; also, the converter 42 is similar to the GPS down converter 614 which is coupled to the GPS antenna 613 to receive GPS signals.

In an alternative embodiment the signal 604 provided by the AFC unit in the communication receiver is an LO which at the proper frequency serves as a reference for the frequency synthesizer 609. In this case no GPS local oscillator is required (shown in Figure 6A as optional for this reason) and this signal 604 will be fed directly to the synthesizer 609 in substitution for the signal 607 from the GPS local oscillator. In this manner, a precise, stable local oscillator clock signal is provided to the GPS downconverter for the downconverter to acquire GPS signals received through a GPS antenna.

In another alternative embodiment, the result of the comparison performed by comparator 605 may be output via interconnect 610a as an error correction to the DSP component 620 which is similar to the DSP chip 32 shown in Figure 1A. In this instance, no error correction signal 610 will be provided indirectly to the frequency synthesizer 609. The automatic frequency control circuit may be implemented using a number of conventional techniques including a phase lock loop or a frequency lock loop or a block phase estimator.

Figure 6B shows another embodiment of a mobile GPS unit for calibrating the GPS local oscillator used to acquire (e.g., downconvert) the GPS signals in the mobile unit of the present invention. The approach is to derive a stable frequency from the receiving circuitry of a communication receiver. Many communication signals, such as digital cellular and PCS signals have carrier frequencies stable to as good as 0.1 parts per million. The receivers for such signals provide, as part of their operation, a phase locking procedure applied to the receiver signal carrier so that such a carrier may be removed allowing the demodulation of the digital data imposed upon the carrier. The phase locking procedure normally produces as part of its process a stable local oscillator which can then be utilized to separately stabilize the local oscillators of a GPS receiver, thereby eliminating expensive components on this receiver.

The communication signal received by the communication receiver 640 may have one of a multiplicity of possible carrier frequencies, depending upon which channel it is tuned to. The first stage (converter 642) of the receiver

downconverts the input signal to a single IF frequency, for example 140 MHz. This downconversion is controlled by the oscillator VCO1 643 which provides an oscillator signal input to the downconverter 642. The output of VCO1 is in turn controlled by the frequency synthesizer 644 which provides an input to oscillators VCO1 643 and VCO2 647. The mixer 646 forms a second stage RF to IF downconverter which is controlled by an input oscillator signal from oscillator 647. The following stage (Costas Loop Demodulator 648 and Temperature Compensated Voltage Controlled Oscillator (TCVCXO) 645) of the communication receiver is a phaselocking circuit whose purpose is to construct a local oscillator signal which is phaselocked to the incoming signal's carrier frequency. For a signal that is phase-shift keyed, a common circuit well known in the art to perform this circuit is the Costas Loop (e.g. see Gardner, Phaselock Techniques, 2nd Edition, John Wiley & Sons, 1979). In Figure 6B the Costas Loop provides a frequency correction voltage to the reference frequency generator TCVCXO 645 which causes the output of TCVCXO 645 to be phase and frequency aligned with the carrier frequency of the IF signal.

The VCO output 645a (from TCVCXO 645) may then be supplied as a reference frequency to a frequency synthesizer 654 used with the GPS downconverter 652 of the GPS receiver portion 650. In this manner the frequency synthesizer produces inputs for local oscillators (VCO3 653 and VCO4 655) for use in the GPS system that has the same frequency stability as that of the received communication signal. The oscillator 653 controls the first stage of the RF to IF downconversion, and the oscillator 655 controls the second stage of the RF to IF downconversion. The mixer 656 forms a second stage RF to IF downconverter which receives a first intermediate frequency from downconverter 652 and provides a second intermediate frequency to the digitizer circuits (shown together with the buffer and GPS processor in block 657).

Note that the above approach is applicable even though the frequency of the received communication signal may vary from one reception time to the next, if the signal is assigned to a different frequency channel.

An alternative to the above approach is shown in Figure 6C. Here a Direct Digital Synthesizer (DDS) 677 integrated circuit is provided with a digital tuning word from the Costas Loop 679, which is also implemented as a digital circuit. This tuning word can also then be supplied to the frequency synthesizer 689 that is

-22-

part of the GPS receiver in order to stabilize its local oscillators. In this case this frequency synthesizer may also utilize a DDS 689b in order to allow precision adjustment of its frequency, an inherent feature of a DDS.

There are alternative hybrid combinations of the above approaches--e.g. a DDS in the communication receiver, but the DDS LO output being fed to the GPS system. The general approach is that a frequency locking or phaselocking circuit in the communication receiver produces either a tuning voltage or local oscillator signals which is fed to a frequency synthesis circuit on the GPS receiver in order to stabilize the local oscillators provided by this system.

It should be noted that the phaselocking circuits in receivers 640 and 670 may be alternatively implemented wholly or in part via digital signal processing means instead of analog means. In this case the input to these circuits may be digitized via an A/D converter and the circuit functions of these blocks may be constructed using hardwired or programmable (i.e. programmable DSP) digital signal processing elements.

Figure 7 illustrates a particular sequence of power management according to one embodiment of the invention. It will be appreciated that there are numerous ways which are known in the art in order to reduce power. These include slowing down the clock provided to a synchronous, clocked component as well as completely shutting down power to a particular component or turning off certain circuits of a component but not others. It will be appreciated, for example, that phase lock loops and oscillator circuits require start up and stabilization times and thus a designer may decide not to power down completely (or at all) these components. The example shown in Figure 7 begins in step 701 in which the various components of the system are initialized and placed in a reduced power state. Either periodically or after a predetermined period of time, the communication receiver in the modem 22 is returned to full power to determine whether commands are being sent from the basestation 10. This occurs in step 703. If a request is received in step 705 for location information from a base unit, the modem 22 alerts the power management circuit in step 707. At this point in time, the communication receiver in the modem 22 may be turned off for either a predetermined period of time or turned off to be turned on periodically again at a later time; this is shown as step 709. It will be appreciated that the communication receiver may maintained at a full power state rather than turning it off at this point



in time. Then in step 711, the power management circuit returns the GPS receiver portion of the mobile unit to full power by powering up the converter 42 and the analog to digital converters 44; if the frequency oscillator 38 was also powered down, this component is powered up at this time and returned to full power and allowed some time to stabilize. Then in step 713, the GPS receiver, including components 38, 42 and 44 receive the GPS signal. This GPS signal is buffered in the memory 46 which has also been returned to full power when the GPS receiver was returned to full power in step 711. After collection of the snapshot information is completed, then the GPS receiver is returned to a reduced power state in step 717; this typically comprises reducing power for the converter 42 and 44 while keeping the memory 46 at full power. Then in step 719, the processing system is returned to full power; in one embodiment, this involves providing full power to the DSP chip 32; it will be appreciated however that if the DSP chip 32 is also providing power management functions as in the case of the embodiment shown in Figure 1C, then the DSP chip 32a is typically returned to full power in step 707. In the embodiment shown in Figure 1A where the microprocessor 26 performs power management function, the processing system, such as DSP chip 32 may be returned to full power at step 719. In step 721, the GPS signal is processed according to the method of the present invention, such as that shown in Figure 3. Then, after completing the processing of the GPS signal, the processing system is placed in a reduced power state as shown in step 23 (unless the processing system is also controlling power management as noted above). Then, in step 725 the communication transmitter in the modem 22 is returned to full power in order to transmit in step 727 the processed GPS signal back to the basestation 10. After completing transmission of the processed GPS signal, such as pseudorange information or latitude and longitude information, the communication transmitter is returned to reduced power state in 729 and the power management system waits for a delay of a period of time such as predetermined period of time in step 731. Following this delay the communication receiver in the modem 22 is returned to full power in order to determine whether a request is being sent from a basestation.

Figure 8 shows a method for deriving Doppler information for satellites in view from the satellite almanac data transmitted to a remote unit according to the present invention. The remote unit receives, in step 801, the satellite almanac data

-24-

and stores this data in the remote unit (e.g., storing it in flash EEPROM).

Optionally, the remote unit may stamp the data with the current date and time in order to determine staleness of the almanac data later as described herein.

In step 803, the remote unit determines the approximate time of day and its approximate position. Using the approximate time and position with the satellite almanac data, the remote in step 805 determines the Doppler of all in view satellites. The remote unit, when receiving the position fix command from the base station, may also receive an identification of satellites in view and use this identification to calculate Dopplers for only these satellites from the almanac data and from the approximate time and position determined in step 803. Although almanac data is provided in a specific form within the transmitted signal from the GPS satellites, it is not necessary that this information be supplied over the communication link in this form. For example, this data can be compressed by reducing the accuracy of the various transmitted quantities. Reduction in accuracy may reduce the Doppler accuracy, but such reduction may still be within the allowed error budget of the GPS receiver. Alternatively, another representation of the almanac data may be preferable, e.g. fitting the satellite position data to a set of curves, such as spherical harmonics. This approach may allow the GPS receiver to more easily compute Doppler from the supplied almanac data.

Approximate Doppler may be computed by computing the range from the remote to the satellites of interest at times separated by an appropriate interval (e.g. 1 second). This is done utilizing the supplied Almanac data and the approximate user position (e.g., based upon the fixed location of the cell site in a cellular phone system). The difference in these ranges is a range rate, which can be divided by the speed of light to yield a Doppler expressed in seconds per second (or another suitable set of units such as nanoseconds per second).

Although the methods and apparatus of the present invention have been described with reference to GPS satellites, it will be appreciated that the teachings are equally applicable to positioning systems which utilize pseudolites or a combination of satellites and pseudolites. Pseudolites are ground based transmitters which broadcast a PN code (similar to a GPS signal) modulated on an L-band carrier signal, generally synchronized with GPS time. Each transmitter may be assigned a unique PN code so as to permit identification by a remote receiver. Pseudolites are useful in situations where GPS signals from an orbiting

satellite might be unavailable, such as tunnels, mines, buildings or other enclosed areas. The term "satellite", as used herein, is intended to include pseudolite or equivalents of pseudolites, and the term GPS signals, as used herein, is intended to include GPS-like signals from pseudolites or equivalents of pseudolites.

In the preceding discussion the invention has been described with reference to application upon the United States Global Positioning Satellite (GPS) system. It should be evident, however, that these methods are equally applicable to similar satellite positioning systems, and in, particular, the Russian Glonass system. The Glonass system primarily differs from GPS system in that the emissions from different satellites are differentiated from one another by utilizing slightly different carrier frequencies, rather than utilizing different pseudorandom codes. In this situation substantially all the circuitry and algorithms described previously are applicable with the exception that when processing a new satellite's emission a different exponential multiplier is used to preprocess the data. This operation may be combined with the Doppler correction operation of box 108 Figure 3, without requiring any additional processing operations. Only one PN code is required in this situation, thus eliminating block 106. The term "GPS" used herein includes such alternative satellite positioning systems, including the Russian Glonass system.

Although Figures 1A, 1B and 1C illustrate a multiplicity of logic blocks that process digital signals (e.g. 46, 32, 34, 26, 30, 28 in Figure 1A), it should be appreciated that several or all of these blocks may be integrated together onto a single integrated circuit, while still maintaining the programmable nature of the DSP portion of such a circuit. Such an implementation may be important for very low power and cost sensitive applications.

It will be appreciated that the various aspects of the present invention, including the use of satellite almanac data at the remote unit to derive Doppler information and including the use of a precision carrier frequency signal to calibrate the output of a GPS local oscillator which is used to acquire GPS signals, may be used in GPS mobile units having architectures such as those described in U.S. Patent Application Serial No. 08/652,833, filed May 23, 1996 by Norman F. Krasner, which application is hereby incorporated herein by reference.

It should also be appreciated that one or several of the operations of Figure 3 may be performed by hardwired logic in order to increase the overall processing

-26-

speed, while retaining the programmable nature of the DSP processor. For example, the Doppler correction capability of block 108 may be performed by dedicated hardware that may be placed between the digital snapshot memory 46 and the DSP IC 32. All other software functions of Figure 3 may in such cases be performed by the DSP processor. Also, several DSPs may be used together in one remote unit to provide greater processing power. It will also be appreciated that it is possible to collect (sample) multiple sets of frames of GPS data signals and process each set as shown in Figure 3 while accounting for the time between the collection of each set of frames.

In the foregoing specification, the invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed is:

1. In a method for determining the position of a remote unit, a process comprising:  
receiving, at said remote unit, a satellite almanac information for a plurality of satellites in view of said remote unit; and  
computing, in said remote unit, a position information for said satellite by using a Doppler information derived from said satellite almanac information.
2. A process as in claim 1, further comprising:  
transmitting said satellite almanac information from a basestation to said remote unit.
3. A process as in claim 2 wherein said satellite almanac information is obtained from a reference storage medium at said basestation.
4. A process as in claim 2 wherein said position information comprises pseudoranges to a plurality of satellites in view of said remote unit, including said satellite.
5. A process as in claim 2 wherein said position information comprises a latitude and longitude which indicates the position of said remote unit.

-28-

6. A process as in claim 4 further comprising:  
transmitting said pseudoranges from said remote unit to said basestation, and wherein said basestation computes a latitude and longitude which indicates the position of said remote unit.

7. A process as in claim 4 further comprising transmitting satellite data information of said satellite to said remote unit, said satellite data information comprising data representative of ephemeris for said satellite.

8. A process as in claim 5 further comprising transmitting satellite data information of said satellite to said remote unit, said satellite data information comprising data representative of ephemeris for said satellite.

9. A mobile unit which uses data representative of GPS signals to provide the position of said mobile unit, said mobile unit comprising:  
a receiver in said mobile unit, said receiver operable for coupling through a communications link to receive a satellite almanac information for a plurality of satellites in view of said mobile unit;  
a processing unit in said mobile unit, said processing unit coupled to said receiver to receive said satellite almanac information and compute a position information for said satellite by using a Doppler information derived from said satellite almanac information.

10. A method of using a basestation for providing a communications link to a mobile GPS unit, said method comprising:  
determining a satellite almanac information for a plurality of satellites in view of said mobile GPS unit;  
transmitting said satellite almanac information to said mobile GPS unit for determination of a Doppler information.

11. A method as in claim 10, wherein said Doppler information represents the Doppler shift of GPS signals from said satellite to said basestation.

-29-

12. A method as in claim 11 wherein said Doppler information approximately represents the Doppler shift of GPS signals from said satellite to said mobile GPS unit.
13. A method as in claim 10 wherein said Doppler information is obtained from a GPS receiver at said basestation and wherein said Doppler information represents the Doppler shift of GPS signals from said satellite to said basestation.
14. A method as in claim 13 wherein said Doppler information approximately represents the Doppler shift of GPS signals from said satellite mobile GPS unit.
15. A method as in claim 14 further comprising:  
receiving a position information from said mobile GPS unit, said position information being received at said basestation such that said basestation obtains a latitude and longitude which indicates the position of said mobile GPS unit.
16. A method as in claim 15 wherein said position information comprises pseudoranges to said plurality of satellites in view of said mobile GPS unit, and wherein said basestation computes said latitude and longitude from said pseudoranges.
17. A method as in claim 15 wherein said position information comprises said latitude and longitude.
18. A method as in claim 10 further comprising:  
transmitting satellite data information of said satellite to said mobile GPS unit, said satellite data information comprising data representative of ephemeris for said satellite.

-30-

19. A process as in claim 1 wherein a processing unit uses said Doppler information to compensate for a Doppler shift of GPS signals from said satellite.
20. A mobile unit as in claim 9 wherein said processing unit uses said Doppler information to compensate for a Doppler shift of GPS signals from said satellite.
21. A mobile unit as in claim 20 wherein said communication link comprises a radio frequency communication medium.
22. A mobile unit as in claim 20 further comprising:  
a transmitter coupled to said processing unit, said transmitter for transmitting said position information.
23. A mobile unit as in claim 22 wherein said position information comprises pseudorange to said plurality of satellites in view of said mobile unit.
24. A mobile unit as in claim 22 wherein said position information comprises a latitude and longitude which indicates the position of said mobile unit.
25. A mobile unit as in claim 20 wherein said processing unit comprises a digital signal processing integrated circuit (DSP) and wherein said DSP processes said GPS signals and said Doppler information using a fast convolution algorithm.
26. A mobile unit as in claim 25 further comprising:  
a transmitter coupled to said processing unit, said transmitter for transmitting said position information.
27. A mobile unit as in claim 9 wherein said receiver is operable to receive satellite data information of said satellite from a source other than said



satellite, wherein said satellite data information comprises data representative of ephemeris for said satellite.

28. A basestation for providing a communication link to a mobile GPS unit, said basestation comprising:

a source of a satellite almanac information for a plurality of satellites in view of said mobile GPS unit;

a transmitter coupled to said source of said satellite almanac information, said transmitter for transmitting through said communications link said satellite almanac information to said mobile GPS unit for determination of a Doppler information.

29. A basestation as in claim 28 wherein said source of said satellite almanac information is a storage unit coupled to said basestation.

30. A basestation as in claim 28 further comprising:

a receiver for receiving a position information from said mobile GPS unit;

a processor coupled to said receiver.

31. A basestation as in claim 28, wherein said Doppler information approximately represents the Doppler shift of GPS signals from said satellite to said basestation.

32. A basestation as in claim 30, wherein said position information is received at said basestation such that said basestation obtains a latitude and longitude which indicates the position of said mobile GPS unit.

33. A basestation as in claim 32, wherein said position information comprises pseudoranges to at least some of said plurality of satellites in view of said mobile GPS unit, and wherein said processor of said basestation computes said latitude and longitude from said pseudorange.

-32-

34. A basestation as in claim 28 wherein said transmitter is also for transmitting satellite data information of said satellite to said mobile GPS unit, said satellite data information comprising data representative of ephemeris for said satellite.

35. A basestation as in claim 31 wherein said basestation and said mobile GPS unit are within approximately 150 kilometers of each other.

36. A method of calibrating a local oscillator in a mobile GPS receiver, said method comprising:

- receiving a precision carrier frequency signal from a source
- providing said precision carrier frequency signal;
- automatically locking to said precision carrier frequency signal and providing a reference signal;
- calibrating said local oscillator with said reference signal, said local oscillator being used to acquire GPS signals.

37. A method as in claim 36 wherein said receiving step comprises extracting said precision carrier frequency signal from a data signal containing satellite data information communicated over a communication link.

38. A method as in claim 37 wherein said satellite data information comprises a satellite almanac information for a plurality of satellites in view of said mobile GPS receiver.

39. A method as in claim 37 wherein said satellite data information comprises data representative of ephemeris for a satellite.

40. A method as in claim 37 wherein said communication link is selected from the group consisting of a two-way pager link or a cellular telephone link or personal communication system or specialized mobile radio or a wireless packet data system.

-33-

41. A method as in claim 37 wherein said communication link is a radio frequency communication medium.
42. A method as in claim 36 wherein said automatic frequency control logic comprises one of a phase lock loop or a frequency lock loop or a block phase estimator.
43. A method as in claim 42 wherein said reference signal provides a reference frequency which is compared to a frequency provided by said local oscillator to calibrate said local oscillator.
44. A mobile GPS receiver comprising:  
a first antenna for receiving GPS signals;  
a downconverter coupled to said first antenna, said first antenna providing said GPS signals to said downconverter;  
a local oscillator coupled to said downconverter, said local oscillator providing a first reference signal to said downconverter to convert said GPS signals from a first frequency to a second frequency;  
a second antenna for receiving a precision carrier frequency signal from a source providing said precision carrier frequency signal;  
an automatic frequency control (AFC) circuit coupled to said second antenna, said AFC circuit providing a second reference signal to said local oscillator to calibrate said first reference signal of said local oscillator, wherein said local oscillator is used to acquire said GPS signals.
45. A mobile GPS receiver as in claim 44 further comprising a comparator coupled to said AFC circuit and to said local oscillator, said comparator comparing said first reference signal and said second reference signal to adjust the frequency of said first reference signal from said local oscillator.
46. A mobile GPS receiver as in claim 45 wherein said AFC circuit comprises a phase lock loop coupled to a receiver which is coupled to said second antenna.

47. A mobile GPS receiver as in claim 44 further comprising a receiver coupled to said second antenna, said receiver for receiving said precision carrier frequency signal from said second antenna, wherein said receiver receives said precision carrier frequency signal with a data signal containing satellite data information communicated through said second antenna.

48. A mobile GPS receiver as in claim 47 wherein said satellite data information comprises a Doppler information of a satellite in view of said mobile GPS receiver.

49. A mobile GPS receiver as in claim 48 wherein said satellite data information comprises an identification of a plurality of satellites in view of said mobile GPS receiver and a corresponding plurality of Doppler information for each satellite of said plurality of satellites in view of said mobile GPS receiver.

50. A mobile GPS receiver as in claim 47 wherein said satellite data information comprises data representative of ephemeris for a satellite.

51. A method of using a basestation to calibrate a local oscillator in a mobile GPS receiver, said method comprising:  
producing a first reference signal having a precision frequency;  
modulating said first reference signal with a data signal to provide a precision carrier frequency signal;  
transmitting said precision carrier frequency signal to said mobile GPS receiver, said precision carrier frequency signal being used to calibrate a local oscillator in said mobile GPS receiver, said local oscillator being used to acquire GPS signals.

52. A method as in claim 51 wherein said data signal contains satellite data information which comprises a satellite almanac information for a plurality of satellites in view of said mobile GPS receiver.

53. A method as in claim 51 wherein said data signal contains satellite data information which comprises data representative of ephemeris for a satellite.

54. A basestation for providing a calibration signal for use in a mobile GPS receiver to calibrate a local oscillator in said mobile GPS receiver, said basestation comprising:

a first source for a first reference signal have a precision frequency;  
a modulator coupled to said first source and to a second source of satellite data information said modulator providing a precision carrier frequency signal;

a transmitter coupled to said modulator, said transmitter for transmitting said precision carrier frequency signal to said mobile GPS receiver, said precision frequency signal being used to calibrate said local oscillator, said local oscillator being used to acquire said GPS signals.

55. A basestation as in claim 54 wherein said precision carrier frequency signal has a first frequency which is substantially different from a frequency of said GPS signals.

56. A basestation as in claim 54 wherein said satellite data information comprises data representative of ephemeris for a satellite in view of said mobile GPS receiver.

57. A basestation as in claim 54 further comprising a processor coupled to said transmitter, said processor instructing said transmitter to transmit to said mobile GPS receiver.

58. A basestation as in claim 57 wherein said processor determines a plurality of satellites in view of said mobile GPS receiver and obtains said satellite data information for each satellite of said plurality of satellites, and wherein said processor instructs said transmitter to transmit to said mobile GPS receiver an identification of said plurality of satellites and said satellite data information.

59. A basestation as in claim 58 wherein said satellite data information comprises Doppler information for said plurality of satellites.

-36-

60. A basestation as in claim 58 wherein said satellite data information comprises data representative of ephemeris for said plurality of satellites.

61. A method of deriving a local oscillator signal in a mobile GPS receiver, said method comprising:  
receiving a precision carrier frequency signal from a source  
providing said precision carrier frequency signal;  
automatically locking to said precision carrier frequency signal and  
providing a reference signal;  
using said reference signal to provide a local oscillator signal to  
acquire GPS signals.

62. A method as in claim 61 wherein said receiving step comprises extracting said precision carrier frequency signal from a data signal containing satellite data information communicated over a communication link.

63. A method as in claim 62 wherein said satellite data information comprises a satellite almanac information for a plurality of satellites in view of said mobile GPS receiver.

64. A method as in claim 62 wherein said satellite data information comprises data representative of ephemeris for a satellite.

65. A method as in claim 62 wherein said communication link is selected from the group consisting of a two-way pager link or a cellular telephone link or personal communication system or specialized mobile radio or a wireless packet data system.

66. A method as in claim 62 wherein said communication link is a radio frequency communication medium.

67. A method as in claim 61 wherein said step of using said reference signal comprises providing said reference signal to a frequency synthesizer and

-37-

producing said local oscillator signal from said reference signal and said frequency synthesizer.

68. A method as in claim 61 further comprising downconverting GPS signals received through a GPS antenna, said downconverting step using said local oscillator signal to downconvert said GPS signals.

69. A method as in claim 61 wherein said step of using said reference signal comprises downconverting GPS signals received through a GPS antenna, said downconverting using said local oscillator signal to downconvert said GPS signals.

70. A mobile GPS receiver comprising:  
a first antenna for receiving GPS signals;  
a downconverter coupled to said first antenna, said first antenna providing said GPS signals to said downconverter, said downconverter having an input for receiving a local oscillator signal to convert said GPS signals from a first frequency to a second frequency;  
a second antenna for receiving a precision carrier frequency signal from a source providing said precision carrier frequency signal;  
an automatic frequency control (AFC) circuit coupled to said second antenna, said AFC circuit being coupled to said downconverter to provide said local oscillator signal which is used to acquire said GPS signals.

71. A mobile GPS receiver as in claim 70 further comprising a frequency synthesizer coupled to said AFC circuit and to said downconverter, said downconverter receiving said local oscillator through said frequency synthesizer.




FIG. 1A






FIG. 1B




Figure 1C




Figure 2A

5/14




Figure 2B

6/14






Figure 3

7/14




Figures 4A, 4B, 4C, 4D, 4E

FIGURE 5A



9/14

FIGURE 5B





10/14




FIGURE 6A

11/14




Figure 6B

12/14





Figure 6C

13/14

FIGURE 7






Figure 8

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/03512

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : H04B 7/185; G01S 5/02

US CL : 342/357; 364/449.7

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 342/357; 364/449.7  
449.9, 449.95

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,153,598 (ALVES, JR.) 06 October 1992, See Figure 1.	1-35
X	US, A, 5,323,322 (MUELLER ET AL) 21 June 1994, See Figure 3	1-35
X	US, A, 4,445,118 (TAYLOR ET AL) 24 April 1984, See Figure 3	1-35
X	US, A, 5,119,102 (BARNARD) 02 June 1992, See Figure 3	1-35
X	US, A, 5,420,592 (JOHNSON) 30 May 1995, See Figure 2	1-71
X	US, A, 4,457,006 (MAINE) 26 June 1984, See column 4, lines 63 +	36-71

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

05 JUNE 1997

Date of mailing of the international search report

11 JUL 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231Authorized officer  
*Theodore Blum*  
THEODORE BLUM

Facsimile No. (703) 305-3230

Telephone No. (703) 305-1833

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/03512

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,365,450 (SCHUCHMAN ET AL) 15 November 1994, See claims 3, 9, and 11	36-71
.	.	.
.	.	.
.	.	.